Test Report for Flicker

Report ID: Strobe test
Catalog: ELED-30-xT-SLP(x=12,24 or 48)
Description: worked with regular and appropriate LED strip according to tested LED driver

Manufacturer: China Factory
Number:
Comments: 5% brightness level

Test Results

Power Supply: U=230.0V, F=50.00Hz, Voltage Modulation: No

Basic

Frequency: 433.743 Hz
Average: 110.621 lm
Maximum: 1838.091 lm
Minimum: 0.000 lm

IEC-Pst

PstLM: 0.283
Evaluate: Acceptable

CIE SVM

SVM: 1.014
Visibility: Visibile

IEEE Std 1789

NM1: 2.381
Modulation: 100.000%
NM2: 7.629
Risk Level: High Risk

ASSIST

Flicker Index: 0.921
Percent Flicker: 100.000%
Mp: 0.265
Dp: 1.499%
d: 75.455%
a: 0.997
fb: 145.248 Hz
Evaluate: Neutral

CA CEC

PAM: 100.000%
PAM(40Hz): 0.865%
PAM(90Hz): 1.068%
PAM(200Hz): 1.852%
PAM(400Hz): 3.032%
PAM(1000Hz): 100.000%



Test Lab: Ecopac(UK)Power Ltd
Operator: ZL
Photometric Type: Luminous Flux
Sample Rate: 50 KS/s
Signal: P2,M18563,

Test Equipment: LFM-5000
Test Time: 2026-08-11 10:15:47
Testing Environment: 26.4 °C, 61.5%
Sample Duration: 60.0 S
According: IESNA 2000, CIE TN 006, etc

Test Report for CIE SVM

Report ID: Strobe test
Catalog: ELED-30-xT-SLP(x=12,24 or 48)
Description: worked with regular and appropriate LED strip according to tested LED driver

Manufacturer: China Factory
Number:
Comments: 5% brightness level

Test Results

Power Supply: U=230.0V, F=50.00Hz, Voltage Modulation: No
Frequency: 433.743 Hz
Maximum: 1838.091 lm
Flicker Index: 0.921
SVM: 1.014

Average: 110.621 lm
Minimum: 0.000 lm
Modulation: 100.000%
Visibility: Visibile





Test Lab: Ecopac(UK)Power Ltd
Operator: ZL
Photometric Type: Luminous Flux
Sample Rate: 50 KS/s
Signal: P2,M18563,

Test Equipment: LFM-5000
Test Time: 2026-08-11 10:15:47
Testing Environment: 26.4 °C, 61.5%
Sample Duration: 60.0 S
According: CIE TN 006:2016

Test Report for IEC Pst

Report ID: Strobe test
Catalog: ELED-30-xT-SLP(x=12,24 or 48)
Description: worked with regular and appropriate LED strip according to tested LED driver

Manufacturer: China Factory
Number:
Comments: 5% brightness level

Test Results

Power Supply: U=230.0V, F=50.00Hz, Voltage Modulation: No
Frequency: 433.743 Hz
Maximum: 1838.091 lm
Flicker Index: 0.921
PstLM: 0.283

Average: 110.621 lm
Minimum: 0.000 lm
Percent Flicker: 100.000%
Evaluate: Acceptable





Test Lab: Ecopac(UK)Power Ltd
Operator: ZL
Photometric Type: Luminous Flux
Sample Rate: 50 KS/s
Signal: P2,M18563,

Test Equipment: LFM-5000
Test Time: 2026-08-11 10:15:47
Testing Environment: 26.4 °C, 61.5%
Sample Duration: 60.0 S
According: IEC TR 61547-1:2020

Test Report for IEEE Std1789

Report ID: Strobe test
Catalog: ELED-30-xT-SLP(x=12,24 or 48)
Description: worked with regular and appropriate LED strip according to tested LED driver

Manufacturer: China Factory
Number:
Comments: 5% brightness level

Test Results

Power Supply: U=230.0V, F=50.00Hz, Voltage Modulation: No
Frequency: 433.743 Hz
Maximum: 1838.091 lm
Flicker Index: 0.921
NM1: 2.381, NM2: 7.629

Average: 110.621 lm
Minimum: 0.000 lm
Modulation: 100.000%
Risk Level: High Risk





Test Lab: Ecopac(UK)Power Ltd
Operator: ZL
Photometric Type: Luminous Flux
Sample Rate: 50 KS/s
Signal: P2,M18563,

Test Equipment: LFM-5000
Test Time: 2026-08-11 10:15:47
Testing Environment: 26.4 °C, 61.5%
Sample Duration: 60.0 S
According: IEEE Std 1789-2015